



PRIZOR VIZTECH LIMITED




PRV-MDV9104-BS

4CH MOBILE DVR OFFLINE

KEY FEATURES


- ◆ 4 CHANNELS HYBRID MDVR
- ◆ H.265 VIDEO COMPRESSION
- ◆ SUPPORTS SD CARD FOR MIRROR RECORDING
- ◆ SUPPORTS HARD DISK FOR MAIN RECORDING
- ◆ SUPPORTS GPS FOR LOCATION TRACKING
- ◆ VIBRATION-RESISTANT DESIGN TO MEET
VARIOUS ENVIROMENT NEEDS
- ◆ GPS LOCATION, ALARM, VEHICLE NO, SPEED, DATE/TIME

MDVR



SPECIFICATIONS

MODEL	PRV-MDV9104-BS
VIDEO & AUDIO	
VIDEO INPUT	4CH VIDEO
OPERATING SYSTEM	EMBEDDED LINUX
VIDEO COMPRESSION	H.265 COMPRESSION
TV SYSTEM	PAL/NTSC
OPERATION	MULTIPLEX
RECORD SETTINGS	
RESOLUTION & FRAME RATE	PAL UPTO 4X1080N@25FPS
	QUALITY MODE: LOWEST, LOW, NORMAL, HIGH& HIGHEST
SCHEDULE	CONTINUOUS & EMERGENCY RECORDING
RECORDING FORMAT	PROPRIETARY FORMAT (RECORDED DATA'S ARE ENCRYPTED WITH USER NAME & PASSWORD)
STORAGE	SDHC CARD (CLASS-6 ARE ABOVE) & HDD SUPPORT UPTO 1TB
ETHERNET	NA
3G/4G	NA
LAN PORT	NA
STORAGE	
STORAGE TYPE & NUMBER OF SLOT	HDD(1 Open bay) & SD card Slot (optional)
STORAGE CAPACITY	HDD-2Tb, 2.5" SATAIII (1TB Support)& SD card 256GB above class 6



SPECIFICATIONS

MODEL	PRV-MDV9104-BS
OVERWRITE MODE	AUTO OVER WRITE FIFO (EMERGENCY RECORDING CAN STARTS AUTOMATICALLY THIS DATA CANNOT BE OVERWRITTEN)
EXTERNAL INTERFACE	
VIDEO OUTPUT	TV-OUT (1 VP-P COMPOSITE VIDEO OUTPUT 75 OHMS) RCA and 1-VGA
AUDIO INPUT	4 channels (4 channels IPC audio input)
AUDIO OUTPUT	1CH RCA
ALARM INPUT	4CH SENSOR INPUT
GPS SENSOR/NETWORK	YES/NA
BEHAVIOUR SENSOR	BUILT IN 3D -GSENSOR
MAX POWER	10-36V / 3000MA (POWER SUPPLY NOT INCLUDED)
GENERAL	
PRODUCT DIMENSIONS	130MM X 147MM X 43MM (W X D X H)
ACCESSORIES	3 PIN POWER CABLE, ALARM CABLE, 3M EXTENDING IR LEAD, REMOTE CONTROL, MICROPHONE, GPSEXTENSION ANTENNA CORD, SOFTWARE CD & QUICK REFERENCE GUIDE.
ENVIRONMENT	
TEMPERATURE & HUMIDITY	-10°C ~ +70°C or -40°C ~ +70°C

