



PRIZOR VIZTECH LIMITED

PRIZ-19FHD-M



19"

KEY FEATURES

- ◆ HD: 1920 * 1080 HIGHER RESOLUTION THAN ORDINARY MONITORS
- ◆ AUTOMATICALLY DETECT THE RESOLUTION OF THE INPUT SIGNAL AT THE BOTTOM LEFT OF THE SCREEN WHEN STARTING UP, AND THE DEFINITION SPEAKS WITH DATA
- ◆ CLARITY: DELICATE AND LIFELIKE , CONVEYING TRUE COLORS, SHOWING TRUE COLORS
- ◆ BRIGHT: IMAGE QUALITY IS IMPROVED, ONLY FOR BETTER PRESENTATION
- ◆ INDUSTRIAL SCREEN, HIGH BRIGHTNESS, HIGH CONTRAST
- ◆ ADOPT HIGH-PRECISION STANDARD REGULATED POWER SUPPLY, SPECIALLY DESIGNED FOR INDUSTRIAL EQUIPMENT, SUPPORT 24 HOURS × 365 DAYS UNINTERRUPTED WORK
- ◆ USING 10 BIT IMAGE CHIP PROCESSING TECHNOLOGY, HIGH-PIXEL PROGRESSIVE SCANNING, FINE AND LIFELIKE PICTURE QUALITY
- ◆ SUPPORT INTELLIGENT 3D NOISE REDUCTION, AFTERIMAGE ELIMINATION FUNCTION, DYNAMIC BRIGHTNESS, CONTRAST COLOR OPTIMIZATION TECHNOLOGY
- ◆ APPLY THE WORLD'S LEADING LIQUID CRYSTAL DRIVE SCHEME TO ACCURATELY RESTORE THE FRONT-END SIGNAL, WITH A STRONG SENSE OF REALITY
- ◆ LIQUID CRYSTAL HAS SMALL SIZE, LOW ENERGY CONSUMPTION, ZERO RADIATION, STABLE IMAGE, NO IMPACT ON EYES, NATURAL AND HEALTHY
- ◆ 5 MS EXTREMELY FAST RESPONSE, AVOIDING IMAGE SMEARING DURING HIGH-SPEED OPERATION
- ◆ USING NANOTECHNOLOGY, THE PICTURE IS MORE THREE-DIMENSIONAL AND TRANSPARENT



1800-123-3699



www.prizor.in



SPECIFICATIONS

MODEL	PRIZ-19FHD-M
Display	
Screen Size	19 Inch
Resolution	1920*1080 (Compatible With 3840*2160/30HZ)
Display Ratio	16:10
Brightness	250cd/m ² (Center Point, Typical Value)
Contrast	1000:1
Viewing Angle	160° /170°
Response Time	5ms(gray To Gray)
Color Depth	16.7m
Function Attributes	
Control Method	Panel
Interface	
Power Input	12v/3a
Input Interface	HDMI/VGA/ USB/ CVBS/Audio Input/
Output Interface	Audio Output
Power Consumption	
Overall Power Consumption	20w
Structure	
Color	Black Body
Material	Flame Retardant Plastic



SPECIFICATIONS

MODEL	PRIZ-19FHD-M
Dimensions	438*291 *46mm, Not Including Foot Height 70 Mm
Package Size	492*105*413mm
Installation Method	Base, Vesa (75mm*75mm)
Net/Gross Weight	2.9kg / 3.6kg
Working Environment	
Temperature	Most Suitable For 20 °C
Humidity	10%-90%rh
Attachment List	
DC Power Supply , Warranty Card, Manual, HDMI Cable (Gift), Base, Self-tapping Screw PA4*12MM (One Bag)	

